

Ceiling&Floor



Specification-R410A 50Hz ON/OFF

Model	Indoor		ALCF-H18/4R1F2-R	ALCF-H24/4R1FA-R	ALCF-H36/4R1FA-R
	Outdoor		AL-H18/4R1F2-R(U)	AL-H24/4R1F3-R(U)	AL-H36/4R1F3-R(U)
Capacity	Cooling/Heating	Btu/h	18000/19100	24000/25250	36000/39920
		kW	5.28/5.6	7.03/7.4	10.55/11.7
Electric Data	Power Supply	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Cooling/Heating Power Input	kW	1.7/1.47	2.15/1.95	3.4/3.17
Performance	Cooling/Heating Current	A	7.5/6.8	9.35/8.5	15/14
	EER/COP	W/W	3.11/3.81	3.27/3.8	3.10/3.69
	Air Flow Volume	m ³ /h	950/700/560	1100/900/760	1600/1260/800
Dimension (W×D×H)	Net	mm	1000×690×235	1000×690×235	1280×690×235
	Packing	mm	1080×770×325	1080×770×325	1360×770×325
Weight	Net	Kg	28	29	36
	Gross	Kg	32	33	42
Stuffing Quantity	20/40/40H	set	60/125/150	60/125/150	50/100/110

Specification-R410A 50Hz ON/OFF

Model	Indoor		ALCF-H36/5R1F2-R	ALCF-H48/5R1FA-R	ALCF-H60/5R1FA-R
	Outdoor		AL-H36/5R1F2-R(U)	AL-H48/5R1F3-R(U)	AL-H60/5R1F3-R(U)
Capacity	Cooling/Heating	Btu/h	36000/39920	48000/52000	55000/60000
		kW	10.55/11.7	14.07/15.24	16.12/17.6
Electric Data	Power Supply	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Cooling/Heating Power Input	kW	3.5/3.24	4.68/4.62	5.55/5.01
Performance	Cooling/Heating Current	A	7.2/7	8.1/8	10/9.5
	EER/COP	W/W	3.01/3.61	3.01/3.45	2.9/3.5
	Air Flow Volume	m ³ /h	1600/1260/800	2150/1900/1350	2150/1900/1350
Dimension (W×D×H)	Net	mm	1280×690×235	1600×690×235	1600×690×235
	Packing	mm	1360×770×325	1680×770×325	1680×770×325
Weight	Net	Kg	36	44	44
	Gross	Kg	42	50.5	50.5
Stuffing Quantity	20/40/40H	set	50/100/110	24/54/54	24/54/54