

Cassette



Specification-50/60Hz DC fan motor

Model	Indoor		ARVCA-H028/R1X	ARVCA-H036/R1X	ARVCA-H045/R1X	ARVCA-H056/R1X	ARVCA-H071/R1X	ARVCA-H080/R1X
Capacity	Cooling	kW	2.8	3.6	4.5	5.6	7.1	8
	Heating	kW	3	4.3	5	6	8	10
Electric Data	Power Supply	V~,Hz,Ph	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1
	Rated Power	W	33.5	33.5	33.5	33.5	40	40
Performance	Air Flow Volume(Hi/Mid/Low)	m ³ /h	700/600/530	700/600/530	700/600/530	700/600/530	1250/1040/910	1250/1040/910
	Noise Level(Hi/Mid/Low)	dB(A)	45/41/35	45/41/35	45/41/35	45/41/35	38/34/30	38/34/30
Dimension (WxDxH)	Net(Body)	mm	570×570×260	570×570×260	570×570×260	570×570×260	835×835×250	835×835×250
	Packing(Body)	mm	655×655×295	655×655×295	655×655×295	655×655×295	910×910×310	910×910×310
	Net(Panel)	mm	650×650×55	650×650×55	650×650×55	650×650×55	950×950×55	950×950×55
	Packing(Panel)	mm	710×710×80	710×710×80	710×710×80	710×710×80	1000×1000×100	1000×1000×100
Weight	Net/Gross(Body)	kg	19/21	19/21	19/21	19/21	24/29	24/29
	Net/Gross(Panel)	kg	2.2/3.7	2.2/3.7	2.2/3.7	2.2/3.7	5.3/7.8	5.3/7.8
Refrigerant Type			R410a	R410a	R410a	R410a	R410a	R410a
Pipe Diameter	Liquid Side	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)	9.52(3/8)
	Gas Side	mm(inch)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.88(5/8)	15.88(5/8)
	Drainage	mm(inch)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Stuffing Quantity	20/40/40H	unit	140/312/354	140/312/354	140/312/354	140/312/354	78/168/184	78/168/184

Specification-50/60Hz DC fan motor

Model	Indoor		ARVCA-H090/R1X	ARVCA-H100/R1X	ARVCA-H112/R1X	ARVCA-H125/R1X	ARVCA-H140/R1X
Capacity	Cooling	kW	9	10	11.2	12.5	14
	Heating	kW	11	12	12.8	13.3	15
Electric Data	Power Supply	V~,Hz,Ph	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1	220~240,50/60,1
	Rated Power	W	65	65	101	101	101
Performance	Air Flow Volume(Hi/Mid/Low)	m ³ /h	1500/1200/1050	1500/1200/1050	1800/1440/1260	1800/1440/1260	1800/1440/1260
	Noise Level(Hi/Mid/Low)	dB(A)	43/39/38	43/39/38	45/42/40	45/42/40	46/43/41
Dimension (WxDxH)	Net(Body)	mm	835×835×250	835×835×250	835×835×290	835×835×290	835×835×290
	Packing(Body)	mm	910×910×310	910×910×310	910×910×350	910×910×350	910×910×350
	Net(Panel)	mm	950×950×55	950×950×55	950×950×55	950×950×55	950×950×55
	Packing(Panel)	mm	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100	1000×1000×100
Weight	Net/Gross(Body)	kg	25/30	25/30	26/31	26/31	26/31
	Net/Gross(Panel)	kg	5.3/7.8	5.3/7.8	5.3/7.8	5.3/7.8	5.3/7.8
Refrigerant Type			R410a	R410a	R410a	R410a	R410a
Pipe Diameter	Liquid Side	mm(inch)	9.52(3/8)	9.52(3/8)	9.52(3/8)	9.52(3/8)	9.52(3/8)
	Gas Side	mm(inch)	15.88(5/8)	15.88(5/8)	15.88(5/8)	15.88(5/8)	15.88(5/8)
	Drainage	mm(inch)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Stuffing Quantity	20/40/40H	unit	78/168/184	78/168/184	68/150/170	68/150/170	68/150/170

Notes:

- 1.Cooling Capacity: Indoor temperature 27°C DB/19°C WB; Outdoor temperature:35°C DB/24°C WB.
- 2.Heating Capacity: Indoor temperature 20°C DB; Outdoor temperature:7°C DB/6°C WB.
- 3.Piping Length:Equivalent piping length: 7.5m, l level difference: 0m.
- 4.Sound level is measured at 1.4m below the unit.
- 5.The above designs and specifications are subject to change without prior notice. Final specifications please refer to technical specification provided by sales representative.