

## Wall-mounted



J type



L type

### Specification-50/60HZ DC fan motor (L type)

Model	Indoor		ARVWM-H022/R1X(L)	ARVWM-H028/R1X(L)	ARVWM-H036/R1X(L)	ARVWM-H045/R1X(L)	ARVWM-H056/R1X(L)	ARVWM-H071/R1X(L)
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	kW	2.5	3	4.3	5	6	8
Electric Data	Power Supply	V~, Hz, Ph	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1
	Rated Power	W	14	14	14	25	25	35
Performance	Air Flow Volume(Hi/Mid/Low)	m <sup>3</sup> /h	650/600/580	650/600/580	650/600/580	850/750/650	850/750/650	1200/950/800
	Noise Level(Hi/Mid/Low)	dB(A)	38/33/27	38/33/27	38/33/27	45/41/35	45/41/35	48/45/39
Dimension (WxDxH)	Net	mm	850×300×198	850×300×198	850×300×198	970×315×235	970×315×235	1100×330×235
	Packing	mm	905×357×267	905×357×267	905×357×267	1010×370×300	1010×370×300	1140×385×300
Weight	Net/Gross	kg	10/13	10/13	10/13	14/18	14/18	16/20
Pipe Diameter	Liquid Side	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas Side	mm(inch)	9.52(3/8)	9.52(3/8)	9.52(3/8)	12.7(1/2)	12.7(1/2)	15.88(5/8)
	Drainage	mm(inch)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Stuffing Quantity	20/40/40H	unit	336/696/812	336/696/812	336/696/812	258/546/637	258/546/637	234/492/492

### Specification-50Hz AC fan motor (L type)

Model	Indoor		ARVWM-H022/4R1A(L)	ARVWM-H028/4R1A(L)	ARVWM-H036/4R1A(L)	ARVWM-H045/4R1A(L)	ARVWM-H056/4R1A(L)	ARVWM-H071/4R1A(L)
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	kW	2.5	3.0	4.3	5.0	6.0	8.0
Electric Data	Power Supply	V~, Hz, Ph	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1
	Rated Power	W	38	38	38	68	68	82
Performance	Air Flow Volume(Hi/Mid/Low)	m <sup>3</sup> /h	650/600/580	650/600/580	650/600/580	850/750/650	850/750/650	1200/950/800
	Noise Level(Hi/Mid/Low)	dB(A)	38/33/27	38/33/27	38/33/27	45/41/35	45/41/35	48/45/39
Dimension (WxDxH)	Net	mm	850×300×198	850×300×198	850×300×198	970×315×235	970×315×235	1100×330×235
	Packing	mm	905×357×267	905×357×267	905×357×267	1010×370×300	1010×370×300	1140×385×300
Weight	Net/Gross	kg	10/13	10/13	10/13	14/18	14/18	16/20
Pipe Diameter	Liquid Side	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas Side	mm(inch)	9.52(3/8)	9.52(3/8)	9.52(3/8)	12.7(1/2)	12.7(1/2)	15.88(5/8)
	Drainage	mm(inch)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Stuffing Quantity	20/40/40H	unit	336/696/812	336/696/812	336/696/812	258/546/637	258/546/637	234/492/492

### Specification- 50/60Hz DC fan motor (J type)

Model	Indoor		ARVWM-H022/NR1DJA	ARVWM-H028/NR1DJA	ARVWM-H036/NR1DJA	ARVWM-H045/NR1DJA	ARVWM-H056/NR1DJA	ARVWM-H071/NR1DJA
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	kW	2.5	3.2	4.3	5.0	6.3	8.0
Electric Data	Power Supply	V~, Hz, Ph	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1	220~240, 50/60, 1
	Rated Power	W	14	14	14	25	25	35
Performance	Air Flow Volume(Hi/Mid/Low)	m <sup>3</sup> /h	650/600/580	650/600/580	650/600/580	850/750/650	850/750/650	1200/950/800
	Noise Level(Hi/Mid/Low)	dB(A)	38/33/27	38/33/27	38/33/27	45/41/35	45/41/35	48/45/39
Dimension (WxDxH)	Net	mm	881×294×194	881×294×194	881×294×194	997×316×227	997×316×227	1132×330×232
	Packing	mm	965×370×282	950×357×257	950×357×257	1067×385×312	1067×385×312	1205×400×317
Weight	Net/Gross	kg	10/13	10/13	10/13	14/18	14/18	16/20
Pipe Diameter	Liquid Side	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas Side	mm(inch)	9.52(3/8)	9.52(3/8)	9.52(3/8)	12.7(1/2)	12.7(1/2)	15.88(5/8)
	Drainage	mm(inch)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)	DN20(R3/4)
Stuffing Quantity	20/40/40H	unit	336/696/812	336/696/812	336/696/812	258/546/637	258/546/637	234/492/492

Notes:

1.Cooling Capacity: Indoor temperature 27°C DB/19°C WB; Outdoor temperature:35°C DB/24°C WB.

2.Heating Capacity:Indoor temperature 20°C DB; Outdoor temperature:7°C DB/6°C WB.

3.Piping Length:Equivalent piping length: 7.5m, l evel difference: 0m.

4.Sound level is measured 1m below the air outlet horizontally and vertically.

5.The above designs and specifications are subject to change without prior notice. Final specifications please refer to technical specification provided by sales representative.